SCIENTIFIC CALCULATOR

EL-501T EL-501XT MODEL

OPERATION MANUAL

PRINTED IN CHINA / IMPRIMÉ EN CHINE / IMPRESO EN CHINA 19HSC(TINSEA297EHZZ)

INTRODUCTION

About the calculation examples (including some formulas and tables), refer to the reverse side of this English manual Refer to the number on the right of each title on the

After reading this manual, store it in a convenient location for future reference. e reference. Some of the models described in this manual may not

be available in some countrie

- Operational Notes

 Do not carry the calculator around in your back pocket, as it may break when you sit down. The display is made of glass and is particularly fragile.

 Keep the calculator away from extreme heat such as on a car dashboard or near a heater, and avoid exposing it to excessively humid or dusty environments.
- excessively humid or dusty environments.
- Since this product is not waterproof, do not use it or store it where fluids, for example water, can splash onto it Raindrops, water spray, juice, coffee, steam, perspiration, etc. will also cause malfunction.
- etc. will also cause malfunction.
 Clean with a soft, dry cloth. Do not use solvents or wet cloth. Avoid using a rough cloth or anything else that may cause scratches.
 Do not drop it or apply excessive force.
 Never dispose of batteries in a fire.
 Keep batteries out of the reach of children.
 This product including accessories may change due to

- This product, including accessories, may change due to upgrading without prior notice.

SHARP will not be liable nor responsible for any inciden by misuse and/or malfunctions of this product and its peripherals, unless such liability is acknowledged by law.

- Press the RESET switch (on the front), with the tip of a ball-point pen or similar object, only in the following cases Do not use an object with a breakable or sharp tip. Note that pressing the RESET switch erases all data stored in When using for the first time
 After replacing the battery
 To clear all memory contents
 When an abnormal condition occurs and all keys are inoperative.


If service should be required on this calculator, use only a SHARP servicing dealer, SHARP approved service facility, or SHARP repair service where available.

Hard Case





Coordinate Conversions Before performing a calculation, select the angular unit



Modify Function

In this calculator, calculation results are internally obtained in scientific notation with up to 12 digits for the mantissa. However, since calculation results are displayed in the form designated by the display notation and the number of decimal places indicated, the internal calculation result may differ from that shown in the display. By using the modify function the internal value is converted to match that of the

function, the internal value is converted to match that of the display, so that the displayed value can be used without change in subsequent operations

BINARY, OCTAL, DECIMAL, AND HEXADECIMAL OPERATIONS (N-BASE) [11]

This calculator can perform the four basic arithmetic operations, calculations with parentheses and memory calculations using binary, octal, decimal, and hexadecimal num-

bers.
When performing calculations in each system, first set the calculator in the desired mode before entering numbers. It can also perform conversions between numbers expressed in binary, octal, decimal and hexadecimal systems.
Conversion to each system is performed by the following keys:

2ndF →BIN : Converts to the binary system. "b" appears

2ndF) →OCT : Converts to the octal system. "a" appears. appears.

2ndF) →DEC : Converts to the decimal system. "b", "a", and "H" disappear from the display.

Conversion is performed on the displayed value when these keys are pressed.

Note: In this calculator, the hexadecimal numbers A – F are entered by pressing $\stackrel{A}{\text{Exp}}$, $\stackrel{B}{\text{yx}}$, $\stackrel{C}{\text{$\checkmark$}}$, $\stackrel{D}{\text{DEG}}$, $\stackrel{E}{\text{In}}$, and log, and displayed as follows:

$$\mathsf{A} \to \mathit{f},\, \mathsf{B} \to \mathit{b}\,,\, \mathsf{C} \to \mathit{\ell}\,,\, \mathsf{D} \to \mathit{d},\, \mathsf{E} \to \mathit{\ell}\,,\, \mathsf{F} \to \mathit{f}$$

In the binary, octal, and hexadecimal systems, fractional In the binary, octal, and hexadecimal systems, fractional parts cannot be entered. When a decimal number having a fractional part is converted into a binary, octal, or hexadecimal number, the fractional part will be truncated. Likewise, when the result of a binary, octal, or hexadecimal calculation includes a fractional part, the fractional part will be truncated. In the binary, octal, and hexadecimal systems, negative numbers are displayed as a complement tive numbers are displayed as a complement

DISPLAY



(During actual use not all symbols are displayed at the same time.) If the value of mantissa does not fit within the range value of mantissa does not fit within the range ±0.00000001 – ±9999999999, the display changes to scientific notation. The display mode can be changed according to the purpose of the calculation.

: Appears when 2ndF is pressed, indicating that the functions shown in orange are enabled.

: Indicates that hyp has been pressed and the hyperbolic functions are enabled. If are hyperbolic functions are enabled. If are hyperbolic functions are enabled.

: Appears when a calculation with parentheses is performed by pressing . ()

DEG/RAD/GRAD: Indicates angular units and changes each time DRG is pressed. The default setting is DEG.

CPLX : Indicates that (2ndF) (CPLX) has been pressed.

Complex number mode is selected STAT : Indicates that (2ndF) (STAT) has been pressed.

Statistics mode is selected : Indicates that (2ndF) (*BIN) has been pressed.

Binary system mode is selected : Indicates that 2ndF) +OCT has been pressed.

Octal system mode is selected. : Indicates that 2ndF) HEX has been pressed. Hexadecimal system mode is selected.


: Indicates that a numerical value is stored in the independent memory.

: Appears when an error is detected

BEFORE USING THE CALCULATOR

Key Notation Used in this Manual

In this manual, key operations are described as follows



Functions that are printed in orange above the key require $\underline{\text{2ndF}}$ to be pressed first before the key. Numbers are not shown as keys, but as ordinary numbers.

Power On and Off

Press [ON/C] to turn the calculator on, and [2ndF] [OFF] to turn it off

Clearing Numbers

- Press ONC to clear the entries except for a numerical value in the independent memory and statistical data.
- Press CE to clear the number entered prior to use of function key In case of one digit correction of the entered number, press
- (right shift key). The exchange key (2ndF 1) is used to exchange the numbe being displayed with the number stored in the working register.

To carry out addition, subtraction, multiplication, and division using complex numbers, press ${\tt 2ndF}({\tt CPLX})$ to select the com-

plex number mode.

• A complex number is represented in the a + bi format. The "a" is the real part while the "bi" is the imaginary part. When inputting the real part, after inputting the number

press a. When inputting the imaginary part, after inputting the number press b. To obtain the result press

Immediately after completing calculation, you can recall the value of the real part with a, and the value of the imaginary part with b.

If the complex numbers are represented as polar coordinates, press 2ndF -xy after they are input with a

Mean of samples (x data)
Sample standard deviation (x data)

Sum of squares of samples (x data)

Sum of samples (x data)

Entered data are kept in memory until (2ndF) (STAT) or (2ndF) (OFF) are pressed. Before entering new data, clear the memory

Correction after pressing DATA:
Reenter the data to be corrected and press 2ndF CD

The number displayed after pressing DATA or 2ndF CD during data entry or correction is the number of samples

• the absolute value of the intermediate result or calculation result is equal to or greater than 1×10^{100} .

an attempt is made to take the square root of a negative

Population standard deviation (x data)

STATISTICAL CALCULATIONS Press (2ndF) (STAT) to select statistics mode.

The following statistics can be obtained:

Nı

Data Entry and Correction

Correction prior to pressing DATA:

Delete incorrect data with ON/C

Statistical Calculation Formulas

the denominator is zero.

SX

 σx

[Data Entry]

[Data Correction]

COMPLEX NUMBER CALCULATIONS

Priority Levels in Calculation This calculator performs operations according to the following

executed in sequence.

Normal mode: 2ndF OFF ON/C

INITIAL SET UP

notation system

100000÷3=

[Floating point] [TAB set to 2]

→[Scientific notation] →[Floating point]

scientific notation system:

Determination of the Angular Unit

GRAD (g)

Mode Selection

The Functions such as sin. x2, and %

(i) Pullicities Section (ii)
(iii) (

Used to perform arithmetic operations and functions. b, a, H, CPLX and STAT are not displayed

Binary, Octal, Decimal, or Hexadecimal system mode:

Complex number mode: <code>2ndF</code> <code>CPLX</code>
Used to perform arithmetic operations with complex numbers.
To clear this mode, press <code>2ndF</code> <code>CPLX</code>.

Statistics mode: <code>2ndF STAT</code>
Used to perform statistical calculations. To clear this mode, press <code>2ndF STAT</code>.
When executing mode selection, statistical data will be cleared even when reselecting the same mode.

By pressing 2ndF) OFF or Automatic power off function, the mode is cleared and returned to the normal mode.

Selecting the Display Notation and Decimal Places

When calculation result is displayed in the floating point system, pressing $\overbrace{\text{F+-E}}$ displays the result in the scientific

Pressing (F+E) once more displays the result again in the

Pressing [PPE] office more displays the result again in the floating point system.

Pressing [2ndF] [TaB] and any value between 0 and 9 specifies the number of decimal places in the calculation result.

To clear the setting of decimal places, press [2ndF] [TaB]

...

N/C 100000 ÷ 3 =

If the value for floating point system does not fit in the

following range, the calculator will display the result using

In this calculator, the following three angular units (degrees, radians, and grads) can be specified.

RAD (rad)

→ DEG (°) →

Press DRG

ERROR AND CALCULATION RANGES

33'333.33 3.33×10°

[15]

33'333.33333

2ndF TAB 2

F*E

F*E 2ndF TAB

(2ndF) (→BIN), (2ndF) (→OCT), (2ndF) (→DEC) or (2ndF) (→HEX

Calculations which are given the same priority level are

If parentheses are used, parenthesized calculations have

precedence over any other calculations.

Parentheses can be continuously used up to 15 times unless pending calculations exceed 4.

erations and function calcula-

An error will occur if an operation exceeds the calculation

ranges, or if a mathematically illegal operation is attempted. In the case of an error, the display will show "E".

An error can be cleared by pressing ONIC.

Calculation Ranges

Within the ranges specified, this calculator is accurate to ±1 of the least significant digit of the mantissa. However, a calculation error increases in continuous calculations due to accumulation of each calculation error. (This is the same for y^x , $x\sqrt{}$, n!, e^x , ln, etc., where continuous

same for y^x, ^x√, nl, e^x, ln, etc., where continuous calculations are performed internally.)
Additionally, a calculation error will accumulate and become larger in the vicinity of inflection points and singular points of functions.

• Calculation ranges
±10-99 ~ ±9.999999999×10-99 and 0.

If the absolute value of an entry or a final or intermediate result of a calculation is less than 10⁻⁹⁹, the value is considered to be 0 in calculations and in the display.

[13]

BATTERY REPLACEMENT

Notes on Battery Replacement

Improper handling of batteries can cause electrolyte leakage or explosion. Be sure to observe the following handling rules:

- Make sure the new battery is the correct type.
 When installing, orient the battery properly as indicated in
- the calculator.

 The battery is factory-installed before shipment, and may be exhausted before it reaches the service life stated in the specifications.

When to Replace the Battery

If the display has poor contrast, the battery requires replacement.

Caution

Fluid from a leaking battery accidentally entering an eye could result in serious injury. Should this occur, wash with clean water and immediately consult a doctor.

Should fluid from a leaking battery come in contact with your skin or clothes, immediately wash with clean water. If the product is not to be used for some time, to avoid damage to the unit from leaking batteries, remove them and store in a safe place. to the unit from leaking batteries, remove them and store in a safe place.

Do not leave exhausted batteries inside the product.

Keep batteries out of the reach of children.

Exhausted batteries left in the calculator may leak and damage the calculator.

Explosion risk may be caused by incorrect handling.

Do not throw batteries into a fire as they may explode

SCIENTIFIC CALCULATIONS

· Calculate in the normal mode

each example, press ON/C to clear the display

[2] **Arithmetic Operations**

The closing parenthesis just before or m+
may be omitted.

When entering only a decimal place, it is not necessary to press before .

Constant Calculations In the constant calculations, the addend becomes a constant. Subtraction and division are performed in the same manner. For multiplication, the multiplicand becomes a

Functions

Refer to the calculation examples of each function.
 For most calculations using functions, enter nur values before pressing the function key.

Random Numbers

Chain Calculations

A pseudo-random number with three significant digits can be generated by pressing [2ndF] [www]. Random number generation is not possible when binary/octal/hexadecimal system mode is set.

Angular Unit Conversions [5] Each time 2ndF DRG+ are pressed, the angular unit changes

in sequence. **Memory Calculations**

This calculator has one independent memory (M). It is available in the normal mode and binary, octal, hexadecimal system mode. The independent memory is indicated by the three keys:

- The independent memory is indicated by the three keys:

 \$\text{STO}\$, \$\text{RCL}\$, \$\text{M+}\$.

 Before starting a calculation, clear the memory by pressing \$\text{ONNC}\$ and \$\text{STO}\$.

 A value can be added to or subtracted from an existing memory value. When subtracting a number from the memory, press \$\text{+/-}\$ and \$\text{M+}\$.

 The contents of the memory are retained even when the
- The contents of the memory are retained even when the calculator is turned off. A value stored in memory will thus remain until it is changed or until the battery runs out.

This calculator allows the previous calculation result to be

used in the following calculation.
The previous calculation result will not be recalled after en-

ng multiple instruction

Time, Decimal and Sexagesimal Calculations [8]

This calculator performs decimal-to-sexagesimal conversion and sexagesimal-to-decimal conversion. In addition, the four basic arithmetic operations and memory calculations can be carried out using the sexagesimal system. Notation for sexagesimal is as follows:



Note: When the calculation or conversion result is converted, a residual may occur.

Replacement Procedure

1. Turn the power off by pressing 2ndF OFF.

2. Remove the battery cover on the back of the unit. (Fig. 1)


3. Remove the used battery by prying it out with a ball-point pen or other similar pointed device. (Fig. 2)

4. Install one new battery. Make sure the "+" side is facing up.

5. Replace the battery cover by reversing the removal procedure.

6. Press the RESET switch (on the front).

 Make sure that the display appears as shown below. If the display does not appear as shown, remove the battery, reinstall it and check the display once again.



Automatic Power Off Function

This calculator will turn itself off to save battery power if no key is pressed for approximately 7 minutes.

SPECIFICATIONS

Operating time:

Calculations: Scientific calculations, binary/octal/

complex number calculations, stastical calculations, etc Internal calculations

Mantissas of up to 12 digits 4 calculations 1.5V -- (DC):
Alkaline battery (LR1130 or equivalent) x 1

Approx. 5000 hours

hexadecimal number calculations.

when continuously displaying 55'555. at 25°C (77°F). Varies according to use and other

factors. 0°C - 40°C (32°F - 104°F) Operating temperature: External dimensions: 72.5 mm (W) × 127 mm (D) × 13 mm (H)

2-27/32" (W) × 5" (D) × 1/2" (H) Weight: Approx. 68 g (0.15 lb)

(Including battery)
Battery × 1 (installed), operation manual, and hard case

FOR MORE INFORMATION ABOUT SCIENTIFIC CALCULATOR

Visit our Web site

http://sharp-world.com/calculator/



CALCULATION EXAMPLES EXEMPLES DE CALCUL ANWENDUNGSBEISPIELE EJEMPLOS DE CÁLCULO ESEMPI DI CALCOLO PÉLDASZÁMÍTÁSOK PŘÍKLADY VÝPOČTŮ **RÄKNEEXEMPEL** LASKENTAESIMERKKEJÄ

[1] ON/C CE	→	
$ \frac{3\times}{4\times5} $ $ 4\times6+7= $	3 × (ON/C) 4 × 5 (CE) 6 + 7 =	3. 0. 5. 0. 31.
134 ↓ 123	134 → → 23	134. 1. 123.
3 ⁴ →4 ³	3 (yx) 4 (2ndF) (‡ (=	64.
[2] + - (× ÷ () +/-	Exp)
45+285÷3=	ON/C 45 + 285 ÷ 3 =	140.
18+6 15-8	(18 + 6) ÷ (15 - 8 = 3.	428571429
42×(-5)+120=	42 × 5 +/- + 120 =	-90.
(5×10 ³)÷(4×10 ⁻³)=	5 Exp 3 ÷ 4 Exp 3 +/- =	1'250'000.
[3]		
34 <u>+57</u> = 45 <u>+57</u> =	34 + 57 = 45 =	91. 102.
79 <u>-59</u> = 56 <u>-59</u> =	79 — 59 = 56 =	20. -3.
56 <u>+8</u> = 92 <u>+8</u> =	56 ÷ 8 = 92 =	7. 11.5
68×25= 68×40=	68 × 25 = 40 =	1'700. 2'720.

[4] \sin \cos \tan \sin^{-1} \cos^{-1} \tan^{-1} π DRG hyp
arc hyp) In $\log e^x 10^x 1/x x^2 x^3 \sqrt{}$
y^{χ} $(\chi \sqrt{y})$ $(3\sqrt{n!})$ (nP_r) (nC_r) $(\%)$

sin60[°]=	ON/C 60 sin	0.866025403
$\cos \frac{\pi}{4} [rad] =$	$\begin{array}{c} \text{DRG} \text{ (2ndF)} \pi \div 4 \\ \text{=} \cos \end{array}$	0.707106781
tan-11=[g]	DRG 1 (2ndF) (tan-1) DRG	50.
(cosh 1.5 + sinh 1.5) ² =	ON/C (1.5 hyp cos + 1.5 hyp sin) X ²	20.08553692
$tanh^{-1}\frac{5}{7} =$	5 ÷ 7 = 2ndF arc hyp tan	0.895879734
In 20 =	20 In	2.995732274
log 50 =	50 log	1.698970004
e ³ =	3 (2ndF) (e ^x)	20.08553692
10 ^{1.7} =	1.7 (2ndF) (10 ^x)	50.11872336
$\frac{1}{6} + \frac{1}{7} =$	$6 \left(2 \text{ndF}\right) \left(1/X\right) + 7 \left(2 \text{ndF}\right)$ $\left(1/X\right) =$	0.309523809
$8^{-2} - 3^4 \times 5^2 =$	8 y ^x 2 +/ 3 y ^x 4 × 5 x ² = -	-2'024.984375
$(12^3)^{\frac{1}{4}} =$	$12 y^x 3 y^x 4$ $2ndF 1/x =$	6.447419591
8 ³ =	8 (2ndF) (X3)	512.
$\sqrt{49} - \sqrt[4]{81} =$	49 \(\bigcup - \ 81 \) 2ndF \(\lambda \sqrt{y} \) 4 =	4.
³ √27=	27 (2ndF) (3/	3.
4! =	4 (2ndF) n!	24.
₁₀ P ₃ =	10 (2ndF) (nPr) 3 =	720.
₅ C ₂ =	5 (2ndF) (nCr) 2 =	10.
500×25%=	500 × 25 (2ndF) % =	125.
120 ÷400=?%	120 ÷ 400 (2ndF) % =	30.
500+(500×25%)=	500 + 25 (2ndF) % =	625.
400-(400×30%)=	400 — 30 (2ndF) % =	280.

• The range of the results of inverse trigonometric functions

- Plage des résultats des fonctions trigonométriques inverses
 Der Ergebnisbereich für inverse trigonemetrische Funktionen
- El rango de los resultados de funciones trigonométricas inversas
 La gamma dei risultati di funzioni trigonometriche inverse
- Az inverz trigonometriai funkciók eredmény-tartománya
 Rozsah výsledků inverzních trigonometrických funkcí

- Omfång för resultaten av omvända trigonometriska funktioner
 Käänteisten trigonometristen funktioiden tulosten alue

	$\theta = \sin^{-1} x, \theta = \tan^{-1} x$	$\theta = \cos^{-1} x$
DEG	$-90 \le \theta \le 90$	$0 \leq \theta \leq 180$
RAD	$-\frac{\pi}{2} \le \theta \le \frac{\pi}{2}$	$0 \leq \theta \leq \pi$
GRAD	$-100 \le \theta \le 100$	$0 \leq \theta \leq 200$

[5] DRG>

$90^{\circ} \rightarrow [rad]$ $\rightarrow [g]$ $\rightarrow [^{\circ}]$	ON/C 90 (2ndF) DRGP (2ndF) DRGP (2ndF) DRGP	1.570796327 100. 90.
$\sin^{-1}0.8 = [^{\circ}]$ $\rightarrow [rad]$	0.8 (2ndF) (sin-1) (2ndF) (DRG)	53.13010235 0.927295218
\rightarrow [g] \rightarrow [°]	2ndF DRG► 2ndF DRG►	59.03344706 53.13010235

[6] RCL STO M+

ANS+5 44+37=ANS

√ANS=

$24 \div (8 \times 2) = $ $(8 \times 2) \times 5 =$	ON/C STO 8 × 2 = STO 24 ÷ RCL = RCL × 5 =	16. 1.5 80.
12+5 -) 2+5 +)12×2 M	ONC STO 12 + 5 = M+ 2 + 5 = +/- M+ 12 × 2 = M+ RCL	17. -7. 24. 34.
\$1= ¥110 ¥26,510=\$? \$2,750=¥?	110 STO 26510 ÷ RCL = 2750 × RCL =	110. 241. 302'500.
r = 3cm $\pi r^2 = ?$	3 STO $2ndF$ π \times RCL X^2 $=$	3. 28.27433388

ON/C 6 + 4 = + 5 =

44 + 37 =

[8] DEG DMS

12°39'18"05 → [10]	ON/C 12.391805 (►DEG)	12.65501389
123.678 → [60]	123.678 (2ndF) DMS	123.404080
sin62°12'24" = [10	01 62.1224 DEG Sin	0.884635235

[9] a b → rθ → xy

$\begin{pmatrix} x = 6 \\ y = 4 \end{pmatrix} \leftarrow \begin{pmatrix} r = \\ \theta = [\circ] \end{pmatrix}$	ON/C 6 a 4 b $2ndF \rightarrow r\theta [r]$ b $[\theta]$ a $[r]$	7.211102551 33.69006753 7.211102551
$\begin{pmatrix} r = 14 \\ \theta = 36[^{\circ}] \end{pmatrix} \begin{pmatrix} x = \\ y = \\ \end{pmatrix}$	14 a 36 b 2ndF →xy [x] b [y] a [x]	11.32623792 8.228993532 11.32623792

[10] MDF TAB

5÷9=ANS	ON/C)(2ndF)(TAB) 1	
ANS×9=	5 ÷ 9 =	0.6
[FIX,TAB=1]	× 9 = *1	5.0
	5 ÷ 9 = (2ndF) (MDF)	0.6
	× 9 = *2	5.4
	(2ndF) (TAB) (•	

*1 5.555555555555×10⁻¹×9 *2 0.6×9

10. 15.


81.

[11] -BIN -OCT -HEX -DEC

DEC(25)→BIN	ON/C 2ndF →DEC 25 2ndF →BIN	11001 b
HEX(1AC) → BIN → OCT → DEC	ONC) (2ndF) ⊕HEX 1AC (2ndF) ⊕BIN 110 (2ndF) ⊕OCT (2ndF) ⊕DEC	0101100 ^b 654 ° 428.
BIN(1010-100) ×11 =	ON/C 2ndF • BIN (1010 - 10	00) 10010 b
HEX(1FF)+ OCT(512)= HEX(?)	ON/C (2ndF) ← HEX 1FF (2ndF) ← OCT) ← 1512 = 2ndF) ← HEX	- 1511 º 349 ^H
2FEC− 2C9E=(A) +)2000− 1901=(B) (C) → DEC	ON/C STO (2ndF) HEX 2FEC - 2C9E M+ 2000 - 1901 M- RCL (2ndF) DEC	34E ^H 6FF ^H A4d ^H 2'637.

[12] CPLX a b $\rightarrow r\theta$ $\rightarrow xy$

(12–6 <i>i</i>) + (7+15 <i>i</i>) – (11+4 <i>i</i>) =	2ndF CPLX 12 a 6 +/- b + 7 (- 11 a 4 b = b	CPLX 0. a 15 b 8. 5. 8.
$6\times(7-9i)\times (-5+8i) =$	6 a × 7 a 9 +/- t 5 +/- a 8 b = b	222. 606.
16×(sin30°+ <i>i</i> cos30° (sin60°+ <i>i</i> cos60°)	÷ 60 sin a 60 cos	30 cos b b 13.85640646 8.
y A	8 a 70 b 2ndF +xy	- TY



(1 + i)	1 (a) 1 (b) (=)	1.
\downarrow	$2ndF$ $\rightarrow r\theta$ $[r]$	1.414213562
$r=?, \theta=?^\circ$	b [θ]	45.

[13] STAT DATA CD \overline{X} Sx Gx n Σx Σx^2

_			
	DATA -	1	STAT
	95	(2ndF)(STAT)	0.
	80	95 (DATA)	1.
	80	80 × 2 (DATA)	3.
	75	75 × 3 (DATA)	6.
	75	50 (DATA)	7.
	75		
	50		
	$\overline{x}=$	\overline{x}	75.71428571
	$\sigma x =$	$2ndF$ σ_x	12.37179148
	n=	n	7.
	$\Sigma x =$	$2ndF$ Σx	530.
	$\Sigma x^2 =$	$2ndF$ Σx^2	41'200.
	sx =	Sx	13.3630621
	$sx^2 =$	X^2	178.5714286

	•	
		STAT
┌ DATA -	2ndF STAT 2ndF STAT	0.
30	30 DATA	1.
40	40 × 2 DATA	3.
40	50 DATA	4.
50		
	50 (2ndF) CD	<i>3</i> .
•	40 × 2 (2ndF) CD	1.
┌ DATA -	1	
30		
45		
45	45 × 3 DATA	4.
45	60 DATA	5.
60		
1		

[14]	$\bar{x} = \frac{\sum x}{n}$	c
	$sx = \sqrt{\frac{\sum x^2 - n\overline{x}^2}{n-1}}$	Σ

 $\sigma x = \sqrt{\frac{\sum x^2 - n\overline{x}^2}{..}}$ $\Sigma x = x_1 + x_2 + \dots + x_n$ $\Sigma x^2 = x_1^2 + x_2^2 + \dots + x_n^2$

[15]

Function Fonction Funktion Función Funzioni Függvény Funkce Funktion Funktio	Dynamic range Plage dynamique zulässiger Bereich Rango dinámico Campi dinamici Megengedett számítási tartomány Dynamický rozsah Definitionsområde Dynaaminen ala
$\sin x$, $\cos x$, $\tan x$	DEG: $ x < 10^{10}$ $(\tan x : x \neq 90 (2n-1))^*$ RAD: $ x < \frac{\pi}{180} \times 10^{10}$ $(\tan x : x \neq \frac{\pi}{2} (2n-1))^*$ GRAD: $ x < \frac{10}{9} \times 10^{10}$ $(\tan x : x \neq 100 (2n-1))^*$
sin-1x, cos-1x	x \le 1
$tan^{-1}x$, $3\sqrt{x}$	$ x < 10^{100}$
In x , $\log x$	$10^{-99} \le x < 10^{100}$
e^{x}	$-10^{100} < x \le 230.2585092$
10 ^x	$-10^{100} < x < 100$
$\sinh x$, $\cosh x$ $\tanh x$	x ≤ 230.2585092
sinh ⁻¹ x	x < 10 ⁵⁰
cosh-1 x	1 ≤ <i>x</i> < 10 ⁵⁰
tanh⁻¹ x	x < 1
χ^2	x < 10 ⁵⁰
x ³	x < 2.15443469×10 ³³

	0 4 10100
√ <i>x</i>	$0 \le x < 10^{100}$
1/ <i>x</i>	$ x < 10^{100} (x \neq 0)$ $0 \le n \le 69^*$
111:	0 ≤ r ≤ n ≤ 9999999999*
nPr	
	$\frac{n!}{(n-r)!}$ < 10^{100}
	$0 \le r \le n \le 9999999999$ *
nCr	0 ≤ r ≤ 69
	$\frac{n!}{(n-r)!}$ < 10 ¹⁰⁰
→D.MS	x < 1 × 10 ¹⁰⁰
→DEG	
$x, y \rightarrow r, \theta$	$\sqrt{x^2 + y^2} < 10^{100}$
	0 ≤ r < 10 ¹⁰⁰
$r, \theta \rightarrow x, y$	DEG: $ \theta < 10^{10}$ RAD: $ \theta < \frac{\pi}{180} \times 10^{10}$
	GRAD: $ \theta < \frac{180}{9} \times 10^{10}$
	DEG \rightarrow RAD, GRAD \rightarrow DEG: $ x < 10^{100}$
DRG ▶	RAD \rightarrow GRAD: $ x < \frac{\pi}{2} \times 10^{98}$
	• $y > 0$: $-10^{100} < x \log y < 100$
	• $y = 0$: $0 < x < 10^{100}$
y^X	• $y < 0$: $x = n$ (0 < x < 1: $\frac{1}{x}$ = 2n-1, $x \ne 0$)*,
	$(0 < x < 1. \frac{1}{x} = 211 = 1, x \neq 0)$, -10 ¹⁰⁰ < x log y < 100
	• $y > 0$: $-10^{100} < \frac{1}{x} \log y < 100 \ (x \neq 0)$ • $y = 0$: $0 < x < 10^{100}$
$x\sqrt{y}$	• $y < 0$: $x = 2n-1$
.,	$(0 < x < 1 : \frac{1}{x} = n, x \ne 0)^*,$
	$-10^{100} < \frac{1}{x} \log y < 100$
(A+Bi)+(C+Di)	A ± C < 10 ¹⁰⁰
(A+Bi)-(C+Di)	B ± D < 10 ¹⁰⁰
$(A+Bi)\times(C+Di)$	(AC – BD) < 10 ¹⁰⁰ (AD + BC) < 10 ¹⁰⁰
	,
/A D3 /O D3	$\frac{AC + BD}{C^2 + D^2} < 10^{100}$
$(A+Bi)\div(C+Di)$	$\frac{BC - AD}{C^2 + D^2} < 10^{100}$
	$C^2 + D^2 \neq 0$
	DEC : x ≤999999999
→DEC	BIN : $1000000000 \le x \le 11111111111111111111111$
→BIN →OCT	OCT : $40000000000 \le x \le 77777777777777777777777$
→HEX	$0 \le x \le 3777777777$ HEX: FDABF41C01 $\le x \le$ FFFFFFFF
	0 ≤ x ≤ 2540BE3FF

Information on the Disposal of this Equipment and its Batteries

IF YOU WISH TO DISPOSE OF THIS EQUIPMENT OR ITS

BATTERIES, DO NOT USE THE ORDINARY WASTE BIN!

DO NOT PUT THEM INTO A FIREPLACE!

1. In the European Union

Seed electrical and electronic equipment and batteries must be
collected and treated SEPARATELY in accordance with law, This
collected and treated SEPARATELY in accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or an accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is a manifestal or accordance with law, This
related is

Manufactured by SHARP CORPORATION 1 Takumi-cho, Sakai-ku, Sakai City, Osaka 590-8522, Japan

mported into Europe by MORAVIA Consulting, spol. s r.o., Olomoucká 83, 627 00 Brno, Czech Republic Visit our Web site

http://www.moravia-consulting.com

For Canada only : For warranty information, please see http://www.sharp.ca/support-product-downloads.aspx Pour le Canada seulement : Pour en lire plus sur la garantie, visitez le http://www.sharp.ca/support-product-do

For Australia / New Zealand only : For warranty information please see <u>www.sharp.net.au</u>



THIS PRODUCT CONTAINS BUTTON BATTERIES. KEEP BATTERIES OUT OF REACH OF CHILDREN.