

SHARP / NEC

**NP-PA1505UL
NP-PA1705UL**

Captivate Audiences with Extreme Brightness LCD Laser Installation Projector



4KUHD
READY



LCD laser installation projectors extreme brightness captivates audiences in conference rooms, auditoriums and sanctuaries

Powerful Tools


- Multi-display support with Picture by Picture/ Picture in Picture
- TileMatrix (internal multi-screen splitter) enables 4Kx2K resolution utilizing 4 projectors without the need for external hardware
- Built-in daisy chain capabilities support multi-display applications
- Seamlessly blend multiple images with integrated edge blending capabilities

Flexible Installations

- Enjoy greater installation flexibility with motorized bayonet style lenses providing quick and easy exchanges. Lens throw distances range from 4.25 to 141ft
- Roll-free installation capabilities make these projectors ideal for almost any install environment, including portrait orientation

Dual Blue Laser Systems


- Images appear immediately after power is on due to instantaneous start up of the laser
- Dual blue laser systems provide best in class white balance over the life of the projector
- Inorganic optical components create longer lifetime and greater peace-of-mind



Filter Free

- Filter free LCD projector
- IP5X certified Sealed LCD cooling system prevents dust from reaching the optics and eliminates the need for a filter
- External air never enters the optical path
- Dust artifacts cannot influence picture quality or decrease image brightness
- LCD Laser Projector that is virtually maintenance free!


Sealed LCD
Cooling System



**IP5X
RATED**
OPTICAL BLOCK

Stacking correction

The industry's first built-in stacking correction capabilities (up-to four projectors) allows the projectors to boost an image's brightness up to 68,000 lumens, which is ideal for larger-sized screens and environments with heavy ambient light. This feature also prevents the complete loss of an image, which can happen when using only one projector.



Edge blending

This function seamlessly blends multiple projected images to display a single high-resolution image.



ProAssist™


Projector management software for installation professionals provides full projector control for multiple screens to create the perfect image. Controls such as input switching, picture, lens, edge blending, uniformity and gamma control are adjustable through the GUI.

ProAssist™



Built-In HDBaseT Support

Simplify your installations with HDBaseT. Optimized for video applications and supporting uncompressed full HD digital video, audio, Ethernet, power and various control signals. With only a single cable (up to 100m) to run, infrastructure and labour costs are reduced, installations are significantly easier, and there is no cable clutter to manage. With uncompressed HD video support, images have never been more stunning. What's more, control signals are contained in the same cable.



Get Connected with a Wide Selection of Inputs

- Multiple Digital computer inputs ensure quick switching between presentations
- Three audio inputs (HDMI1™ & HDMI2™ and HDBaseT) make it easy to add sound to enhance your presentations

Remote control

Wired and wireless backlit remote allows you to adjust for complete control of the projector's menu structure in a well lit or dark environment. Direct controls such as lamp mode, aspect ratio, volume and input selection eliminates multiple button pushes.



Digital Inputs

Among the PA Series' wide selection of inputs are dual HDMI w/HDCP and HDBaseT w/HDCP for connecting to high-definition sources such as Blu-ray players, cable boxes, satellite receivers and personal computers.



HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

Cable Cover

This included accessory creates a clean look for your installation, while hiding signal cables and the power cord.




Advanced Software Features


Geometric Correction

Projecting an image isn't confined to a standard flat screen or wall with the Sharp/NEC PA Series. Geometric correction allows these models to project an image on spheres, cylinders, corner angles and many more non-standard surfaces.


Vertical cylindrical
convex screen



Horizontal cylindrical
concave screen



Vertical cylindrical
concave screen




Corner



Screen Splitter


Sharp/NEC is committed to bringing the latest and greatest innovation to projectors. Multi-Display capabilities and TileMatrix technologies are integrated into the new PA Series projectors. This processing is all done internally and therefore eliminates the additional hardware typically required to produce a beautiful 4K resolution image.



Screen Splitter (Multi-Display) by Daisy Chain

Roll Free

When installation requirements dictate the projector needs to be placed at different angles the PA Series with Roll Free (360°) capabilities assures it is the correct projector of choice.



Unique Features

Variable audio-out enables the remote control to be used to adjust the volume of self-powered external speakers that are connected to the projector. In stand-by mode, the audio-out stays active, allowing the last input used to pass to the self-powered external speakers.

Advanced AccuBlend™ ensures detailed images when non-native resolution sources are connected to the projector

64-step image magnification with location control

Built-in HTTP page for control and monitoring over a LAN network. Email notification of error messages or lamp end-of-life can be sent to remote locations.

Warranty

Registered owners receive a five (5) years or 20,000 hours (whichever comes first) parts and labour warranty.

In the Box


Remote control, batteries, power cord, cable cover, user's manual on CD-ROM, quick start guide, product registration card.

Accessories

RMT-PJ40	Replacement Remote Control
Optional Lenses	NP53ZL, NP54ZL, NP55ZL
IPJ2000CM	Ceiling Mount
AEC0305	Adjustable Extension Column, 3' - 5'

Ordering Model Numbers

NP-PA1505UL-B	NP-PA1705UL-B
NP-PA1505UL-W	NP-PA1705UL-W



		NP-PA1505UL	NP-PA1705UL
Light Output (lumens)	Centre	15,000	17,000
	Normal	14,000	16,000
	ECO Mode OFF	13,500	15,300
Resolution	Native	WUXGA 1920 x 1200	
	Maximum	4K 4096 x 2160	
Contrast Ratio (up-to)		3,000,000:1 (with Dynamic Contrast)	
Laser Life (up-to)		20,000 hours	
Screen Size (diagonal)		1.52 to 12.7m, NP53ZL, NP54ZL, NP55ZL	
Throw Ratio	NP53ZL	0.86 - 1.25:1	
	NP54ZL	1.24 - 2.01:1	
	NP55ZL	1.98 - 3.95:1	
Projection Distance		3.58 to 141 ft. / 1.09 to 43m	
Projection Angle		5.8 to 18.1° tele / 11.4 to 25.8° wide	
Lens*	Motorized		
	Zoom	NP53ZL	1.45x
		NP54ZL	1.62x
		NP55ZL	1.99x
	Motorized		
	Focus	NP53ZL	Motorized zoom / focus, F=1.8 to 2.24, f= 19.0 - 27.6mm, 3.7 lbs. / 5.3 kg
		NP54ZL	Motorized zoom / focus, F=1.8 to 2.24, f= 27.7 - 44.9mm, 3.7 lbs. / 4.5 kg
		NP55ZL	Motorized zoom / focus, F=1.84 to 2.58, f= 43.8 - 87.2mm, 3.7 lbs. / 5.4 kg
	Shift	+/- 25% horizontal, +/- 65% vertical	
	Shutter	Laser Shutter	
Keystone Correction		+/- 40° horizontal, +/- 30° vertical	
Synchronization Range	Horizontal	24-153kHz	
	Vertical	50-120Hz	
Supported Video Standards		NTSC, NTSC4.43, PAL, PAL-60, PAL-M, PAL-N, SECAM	
SD/HD Video Signal Compatibility		480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K	
PC Signal Compatibility		VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, Quad HD	
Macintosh Compatibility		Yes	
Input Terminals	RGB1 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)	
	RGB2 (digital)	HDMI (V2.0) w/HDCP (V1.4/2.2)	
	RGB3 (digital)	HDBaseT w/HDCP (V1.4/2.2)	
	RGB4 (digital)	3G SDI (SMPTE ST 424M / SMPTE 292M)	
Output Terminals	Monitor Out	HDBaseT Repeater	
	Audio Out	Stereo Mini Jack	
External Control		RS-232, IR, Wired Remote, HDBaseT, DDC/Ci, RJ-45, USB (USB 2.0)	
Sync Compatibility		Separate Sync / Composite Sync / Sync on G	
Power Requirements		100-240V AC, 50/60 Hz	
Input Current		11.6A - 5.1A	12.8A - 5.6A
Power Consumption	(Normal/Silent Mode/ Network Standby/ Standby)	960W / 855W / 0.4W / 0.15W	1035W / 855W / 0.4W / 0.15W
Product Dimensions (WxDxH)		23.6 x 19.3 x 9.4 in. / 599 x 490 x 238 mm	
Net Weight		63.7 lbs. / 28.9 kg	
Shipping Dimensions (WxDxH)		29.1 x 24.8 x 15.0 in. / 739 x 629 x 382 mm	
Gross Weight		71.9 lbs. / 32.6 kg	
Fan Noise		38 dB normal / 35 dB silent mode	43 dB normal / 37 dB silent mode
Regulations	USA	USA UL60950-1: 2 nd edition, FCC Part 15 Subpart B (ANSI C63.4.2014)	
	Canada	CAN/CSA C22.2 No.62368-1-18, 3 rd Edition, ICES-003 Issue 7 (ANSI C63.4-2014)	
Operating	Temperature	32-113°F / 0-45°C	
	Humidity	20% - 80% (non-condensing)	
Storage	Temperature	14-122°F / -10 50°C	
	Humidity	20% - 80% (non-condensing)	
Ordering Model Number		NP-PA1505UL-B, NP-PA1505UL-W	NP-PA1705UL-B, NP-PA1705UL-W

* Lens does not ship with the projector. Additional accessories are available, including screens, carts, mount accessories and replacement cables. Visit www.sharp.ca for details.



SHARP / NEC

SHARP ELECTRONICS OF CANADA LTD.
335 Britannia Road East, Ste. 101
Mississauga, Ontario L4Z 1W9
1-800-567-4277 • www.sharp.ca

Printed in Canada.
VSG-VS-PA-E-PDF-09/2023

Sharp is a registered trademark of Sharp Corporation. HDMI, the HDMI Logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.